

Docket No.: ZM466/05048  
Inventor: Champlin  
Application. No.: 10/692,050

IN THE CLAIMS

- Initial appearance Dr*
1. (Previously Presented) An electric pole saw, comprising:  
an electric chain saw having a handle, a main body, a trigger, and a power cord;  
a pole member having an upper end and a lower end;  
a bracket provided near said upper end of said pole member for receiving said handle of  
said electric chain saw and releasably mounting said chain saw on said pole member adjacent  
said upper end thereof, comprising two rigid mounting bracket halves, one of which is fastened  
to said pole member near said upper end of said pole member, said bracket halves having surface  
features that generally conform to the opening and contour created between said handle and said  
main body of said chain saw, a trigger depression device operative to support said trigger of said  
saw in a depressed "on" position and a single point fastening means for releasably securing said  
bracket halves to said chainsaw handle.
  2. (original) The pole saw of Claim 1, wherein said bracket halves each further  
comprise one or more complementary interlocking features to control twisting or angular  
movement between said two bracket halves.
  3. (original) The pole saw of Claim 1, wherein said trigger depression device is  
integral to at least one of said mounting bracket halves.
  4. (original) The pole saw of Claim 1, wherein said mounting bracket halves are  
made from molded plastic material.

Docket No.: ZM466/05048  
Inventor: Champlin  
Application. No.: 10/692,050

5. (original) The pole saw of Claim 1, wherein said mounting bracket halves are made from cast metal material.
6. (canceled)
7. (Previously Presented) The pole saw of Claim 1, wherein said single point fastening means comprises a hand tightenable fastener which requires no external tools to assemble and disassemble.
8. (Previously Presented) The pole saw of Claim 1, further comprising an electrical extension cord disposed within said pole member having an end extending from said upper end of said pole member releasably connectable to said power cord of said chain saw, and having an opposite end releasably connectable to an electrical power supply, and a remote switch mounted on said pole member operative when depressed to transmit electrical power to said chain saw and operative when released to stop transmission of electrical power to said chain saw.
9. (original) The pole saw of Claim 1, wherein said electric chain saw further comprises a knuckle guard.
10. (Previously Presented) In an electric pole saw comprising an electric chain saw having a handle, a main body, a trigger, and a power cord and a pole member having an upper end and a lower end, an improved chain saw mounting bracket assembly provided near said upper end of said pole member for receiving said handle of said electric chain saw and releasably mounting said chain saw on said pole member adjacent said upper end thereof, providing control of angular movement or twisting between the bracket halves and angular movement between the chain saw portion and pole member portion, comprising:

Docket No.: ZM466/05048  
Inventor: Champlin  
Application No.: 10/692,050

two rigid mounting bracket halves, one of which is fastened to said pole member near said upper end of said pole member, said bracket halves having surface features that generally conform to the opening and contour created between said handle and said main body of said chain saw and one or more complementary interlocking features disposed on the surface of each said bracket half that faces said chain saw when said bracket is assembled, a trigger depression device operative to support said trigger of said saw in a depressed "on" position and a single point fastening means for releasably securing said bracket halves to said chainsaw handle.

11. (original) The pole saw of Claim 10, wherein said trigger depression device is integral to at least one of said mounting bracket halves.

12. (original) The pole saw of Claim 10, wherein said mounting bracket halves are made from molded plastic material.

13. (original) The pole saw of Claim 10, wherein said mounting bracket halves are made from cast metal material.

14. (canceled)

15. (Previously Presented) The pole saw of Claim 10, wherein said single point fastening means comprises a hand tightenable fastener which requires no external tools to assemble and disassemble.

16. (original) The pole saw of Claim 10, wherein said electric chain saw further comprises a knuckle guard.

Claims 17-21. (Cancelled)

Docket No.: ZM466/05048  
Inventor: Champlin  
Application. No.: 10/692,050

22. (Previously Presented) An electric pole saw, comprising:  
a pole having a bracket proximate one end of said pole;  
a powerhead comprising a handle and at least one handle opening;  
said bracket comprising a first portion and a second portion;  
one of said first portion and said second portion having an outwardly extending feature substantially conforming to said at least one handle opening;  
said first and second portions of said bracket having interlocking features and a single point fastener.

Claims 23-24 are cancelled.